

AirTalk XS mit PTT 19

Positionierung des Headsets

Zum Anpassen des Kopfbügels den Bügel einfach in Höhe der Bügelführung in die gewünschte Richtung schieben. Der Einrastmechanismus hält den Bügel sicher in der gewünschten Position. [Abb. 1]

Das Headset aufsetzen und die Haare dabei so zur Seite streichen, dass die Ohrmuschel auf der Mitte des freien Ohres platziert werden kann und das Ohrpolster bequem sitzt. Der Gegenhalter wird über dem anderen Ohr platziert. [Abb. 2]

Das Headset ist mit einem NC-Mikrofon (Noise-Cancelling-Mikrofon) ausgestattet. Um eine optimale Geräuschunterdrückung zu erreichen, ist eine exakte Positionierung des Mikrofons erforderlich. Die Mikrofonaufnahme sollte sich dabei ca. 1-2 cm vor ihrem Mund befinden. Durch das schwenkbare Mikrofon lässt sich der Kopfhörer links-/ wie auch rechtsseitig tragen. [Abb. 3 und Abb. 4]

PTT (Push-To-Talk)

Zum Senden eines Funkspruchs die PTT-Taste betätigen. Das VCS-System schaltet von Empfang auf Senden. Nach Übermittlung der Information die PTT-Taste lösen. Das Headset kehrt automatisch in den Empfangsbetrieb zurück. [Abb. 5]

Kleiderclip

Befestigen Sie den Kleiderclip an einer geeigneten Stelle ihrer Oberbekleidung. Der Kleiderclip sorgt für den korrekten Sitz des Headsets und nimmt das Gewicht des Anschlusskabels auf. Die Kabellänge zwischen Headset und Clip sollte dabei ausreichend bemessen werden, um Einschränkungen bei der Kopfbewegung auszuschließen. [Abb. 6]

Wechseln der Polster

Um die Ohrpolster auszutauschen, Hörmuschel festhalten und das alte Ohrpolster vorsichtig abziehen. Das neue Ohrpolster vorsichtig auf die Ohrmuschel drücken bis es mit einem hörbaren Klicken einrastet (nur bei Ohrpolstern Größe S). Zum Wechseln des Schläfenpolsters den Kopfbügel festhalten und das alte Polster abziehen. Die Schutzfolie vom neuen Polster abziehen und dieses in den Gegenhalter einkleben. Zum Wechseln des Spacer-Polsters, Spacer festhalten und das alte Polster abziehen. Schutzfolie vom neuen Polster abziehen und in den Spacer einkleben. [Abb. 7 und Abb. 8]

Persönliche Kennzeichnung

Auf der Innenseite der Kopfbügelführung befindet sich eine Aussparung für die Aufnahme eines Namensetiketts. Namensetikett beschriften und in die Aussparung einlegen. Anschließend das transparente Plättchen in die Aussparung drücken. Zum Wechseln des Etiketts, das transparente Plättchen mit einem spitzen Gegenstand aus der Aussparung entfernen, neues Etikett einlegen und transparentes Plättchen wieder in die Aussparung drücken. [Abb. 9]

Windschutz

Zum Wechseln des Windschutzes ziehen Sie diesen vom Mikrofon ab und den neuen Windschutz vorsichtig über. [Abb. 10]

Spacer

Der Spacer ermöglicht die Wahrnehmung der Umgebungsgeräusche bei aufgesetztem Headset. Durch Verschieben entlang der Bügelführung ist eine optimale Positionierung möglich. [Abb. 10]

Anschluss

Verbinden Sie das Headset über die Steckverbindung mit ihrem System [Abb. 11]. Das Headset ist sofort einsatzbereit. Achten Sie beim Verbinden darauf, die Lautstärkeeinstellung der Geräte auf das Minimum zu reduzieren. [Abb. 12]

Pflege und Entsorgung













Das Headset sollte gelegentlich mit einem weichen, mit Wasser angefeuchteten Tuch abgewischt werden. Verwenden Sie zur Reinigung keinen Alkohol oder andere lösungsmittelhaltige Reiniger. Aus Hygienegründen empfehlen wir, die Ohrpolster und den Windschutz alle drei Monate zu wechseln.

Werfen Sie das Gerät am Ende seiner Lebenszeit nicht in den normalen Hausmüll. Erkundigen Sie sich nach den Möglichkeiten einer umweltgerechten Entsorgung.

ACHTUNG

Prüfen Sie vor jeder Inbetriebnahme die Lautstärkeeinstellungen ihrer Geräte und vermindern Sie diese falls notwendig. Zu laute Signale können auf Dauer zu Gehörschäden führen.

Die technischen Daten für dieses Headset entnehmen Sie bitte dem Datenblatt AirTalk XS PTT19, welches auf unserer Internetseite www.imtradex.de zum Download bereit steht.



AirTalk XS with PTT 19

Adjusting the headset

To adjust the headband according to your requirement, extend or reduce the length of the headbands to a comfortable position. The click-stop keeps the headband in this position. [Fig. 1]

Put the headset on and move your hair, to uncover your ears. Now place the speaker in the middle of the ear in a way that the ear cushions fit comfortable. Place the T-bar support pad just above your free ear. [Fig. 2]

The headset is equipped with an NC-microphone (Noise-Cancelling-Microphone). This reduces catching up environmental noises and within allows transmitting your speech more clearly. To achieve an optimum noise reduction, it is of great importance that the microphone is positioned precisely. Please position the microphone capsule about 1 cm in front of your mouth. The adjustable microphone allows wearing the boom either on the right or left side of the headset. [Fig. 3 and Fig. 4]

PTT (Push-To-Talk)

To transmit a radio message, press the push button of the PTT. The headset will switch from reception mode to transmission mode. After sending the information, release the PTT-Button. The headset automatically returns to „reception“ mode. To adjust the volume, just move the slider on the side of the PTT. [Fig.5]

Cloth clip

Add the cloth clip at a convenient place on your shirt. The cloth clip assists to keep the headset properly positioned. It takes over the weight of the cable and within increases the wearing comfort of the headset. Please take care that the cable between clip and headset stays long enough so that the head can be turned easily without restrictions. [Fig. 6]

Replace the cushions

To replace the ear cushion take the ear piece and pull of the cushion. Carefully encase the new cushion on the ear piece until it fits completely. To replace the cushion of the counter holder, please pull off the old cushion. Then remove the protection film from the new cushion and fix it on the counter holder. To change the spacer-cushion, proceed as with the counterholder. [Fig. 7 and Fig. 8]

Personalization

On the inside of the headband is a name tag where you can put a label inside. Just lift the plastic cover, insert your label and place the cover back into place. To replace the label, simply lift the cover with a pointed object, insert the new label and click the cover back into place. [Fig. 9]

Windscreen

To replace the windscreen, draw it off the microphone and gently replace it by a new one. [Fig. 10]

Spacer

The spacer allows the perception of ambient noise when wearing the headset. By sliding along the guide bracket it allows optimum positioning. [Fig. 10]

Connection

Connect the headset via the plug connection with your System. The headset can be used immediately after the successful connect. Ensure that the volume of the devices are set to minimum before connecting your devices [Fig. 12]

Care and disposal

Occasionally clean the headset with a soft cloth only moistened with water. Strictly avoid using alcohol, detergents or cleaning agents for cleaning. For hygiene reasons, we recommend changing the ear- / temple cushions and the windscreen every three months.

Do not dispose of the device at the end of its life in the normal household waste. Enquire about the options for environmental righteous disposal.

ATTENTION

Before using, please always check the volume of your devices and reduce it if required. Too loud signals may damage your hearing in the long run.

Further technical data of this headset are available on the datasheet AirTalk XS PTT 19, which you can download on our website www.imtradex.com.